



**SEAL TITE®**

# SEAL TITE® 1101

## Dry PTFE packing

In technical collaboration with INNOVATIVE ADHESIVE INC., USA

**SEAL TITE® 1101** is dry PTFE fibre packing without any additional lubricant. It is non-toxic and has low friction, which can do minimal impact on the shaft or sleeve in rotating applications.



### APPLICATION

Valve, pump and all corrosive media. For all concentrated alkalis, acids, oils, solvent. Ideal packing for mixer, dryers, agitators and air compressors.



### ADVANTAGES

- Low co-efficient of friction.
- Maintained density and resiliency ensures excellent leakage control and prevent solid embedment.
- Excellent chemical resistency.



### TECHNICAL DATA

	Pressure (bar)	Shaft speed (m/s)
Static	250	-
Rotating	20	15
Reciprocating	50	5
Temperature(°C)	-60 to +260	
	pH 0-14	

### SPOOL ORDERING INFORMATION

SIZE	mm	3	5	6	6.5	8	9.5	10	11	12	12.5	14	16	19	20	22	25.5
	inch	1/8	3/16	-	1/4	5/16	3/8	-	7/16	-	1/2	9/16	5/8	3/4	-	-	1
PACKAGED (±5%)	kg	1	1	1	1	1	1	1	1	1	1	-	-	-	-	-	-
		-	-	2	2	2	2	2	2	2	2	2	2	2	-	-	-
		-	-	-	-	-	-	-	-	-	5	5	5	5	5	5	5

\*customized size and length available on request.