



SEAL TITE®

ePTFE Universal Rope (with and without oil)

In technical collaboration with INNOVATIVE ADHESIVE INC., USA

SEAL TITE® ePTFE Universal Rope is soft, pliable and flexible sealing gasket material with microfibre structure in multi directional expansion. It is a versatile product for sealing applications. It is manufactured from 100% pure PTFE. The exceptional malleableized structure of expanded PTFE can adapt sealing surfaces, compensate for the damaged sealing surfaces and seals them at very low stresses.



APPLICATION

Static applications for flange and fume ducts, concrete lids and glass joints, heat exchanger, chemical reactors, handand manholes, glass line flanges, hydraulic, pneumatic and water systems, pharma and food processing equipments.





- Quick and simple installation. Easy to install at critically low space area.
- It has excellent thermal and chemical stability, no-ageing, non-toxic and biologically inert.
- Excellent resistance to creep and cold flow It has high sealability at very low stresses.



TECHNICAL DATA

- 100% pure PTFE without any fillers and pigments.
- pH 0-14 (except molten alkali and elemental fluorine)
- Temperature ranges -60 °C to +260°C
- Pressure ranges from Vacuum to 20bar
- Density 0.8 gm/cc (± 0.1)

| | SIZE | mm | 3 | 5 | 6 | 8 | 10 | 12.5 | 14 | 16 | 19 | 20 | 22 | 25 |
|--|----------------|------|-----|------|----|------|----|------|------|-----|-----|----|----|----|
| | | inch | 1/8 | 3/16 | - | 5/16 | - | 1/2 | 9/16 | 5/8 | 3/4 | - | - | 1 |
| | PACKAGED (±5%) | mtr | 50 | 20 | 20 | 20 | - | - | - | - | - | - | - | - |
| | | | - | - | 10 | 10 | 10 | 10 | 10 | 10 | - | - | - | - |
| | | | - | - | - | - | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |

^{*}customized size and length available on request.



303, Atlantis K-10, Opp. Swagat Petrol Pump, Vikram Sarabhai Marg, Wadiwadi, Vadodara -390023. email: info@ptfetapeindia.com